## **Technical specification**

## Unique SSV/7000



1 of 1

19-8-2025

Page

Date

Project ref. Asepti (Nederland) B.V. 7001 Model Unique SSV - Standard

No. of units 1

Item number 9613320030

Configuration code SSV(1):7619200SW1H152SRSSENNNN

Name VALVÉ UNIQUE SSV 38/1.5 200

Description WELD NC 0.8/BLASTED EPDM MAINTAINABLE

Customs statistical no 84818073

Valve basics

Valve function	Shut off
Actuation function	Normally closed
Manual	No
Aseptic	No
Tank outlet	No
Supplied with flange	No
Regulating manual	No
Regulating	No
Kv-value	No
Positioner w display	None

Valve body

Port size	38mm / 1½ Inch
Pipe standard	ISO
Body combination	200
Tangential	No
Tangential orientation	No
Y-body	No
Port A	Welding ends
Port B	Welding ends

**Product wetted seals** 

· · · · · · · · · · · · · · · · · · ·	
Elastomer	EPDM
Plug Seal TR	None

**Actuator** 

Actuator		
Long Stroke	No	
Two step	No	
Maintainable	Yes	
High pressure	No	
Low air pressure	No	
Pressure relief	No	

**Options** 

Surface Finish ID	0.8
Surface Finish OD	Blasted
Atex approved	No

This document and its content is owned by Alfa Laval Corporate AB and protected by laws governing intellectual property and thereto related rights. It is the responsibility of the user of this document to comply with all applicable intellectual property laws. Without limiting any rights related to this document, no parts of this document may be copied, reproduced or transmitted in any form or by any means (electronic, mechanical, photocopying, recording or otherwise), or for any purpose, without the expressed permission or authorized by Alfa Laval Corporate AB. Alfa Laval Corporate AB will enforce its rights related to this document to the fullest extent of the law, including seeking of criminal prosecution.