

Technical specification



Unique SSV/7000

| | |
|------------------------|---------------------------------------|
| Project ref. | Asepti (Nederland) B.V. 7001 |
| Model | Unique SSV - Standard |
| No. of units | 1 |
| Item number | 9613320535 |
| Configuration code | SSV(1):7619200SW1D252SRSSSENNNN |
| Name | VALVE UNIQUE SSV DIN-25 200 |
| Description | WELD NC 0.8/BLASTED EPDM MAINTAINABLE |
| Customs statistical no | 84818073 |

| | |
|------|-----------|
| Page | 1 of 1 |
| Date | 19-8-2025 |

Valve basics

| | |
|----------------------|-----------------|
| Valve function | Shut off |
| Actuation function | Normally closed |
| Manual | No |
| Aseptic | No |
| Tank outlet | No |
| Supplied with flange | No |
| Regulating manual | No |
| Regulating | No |
| Kv-value | No |
| Positioner w display | None |

Valve body

| | |
|------------------------|--------------|
| Port size | DIN-25 |
| Pipe standard | DIN |
| Body combination | 200 |
| Tangential | No |
| Tangential orientation | No |
| Y-body | No |
| Port A | Welding ends |
| Port B | Welding ends |

Product wetted seals

| | |
|--------------|------|
| Elastomer | EPDM |
| Plug Seal TR | None |

Actuator

| | |
|------------------|-----|
| Long Stroke | No |
| Two step | No |
| Maintainable | Yes |
| High pressure | No |
| Low air pressure | No |
| Pressure relief | No |

Options

| | |
|-------------------|---------|
| Surface Finish ID | 0.8 |
| Surface Finish OD | Blasted |
| Atex approved | No |